

500,985

Rec'd PCT/PTO 06 JUL 2004 10/500985

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
17 July 2003 (17.07.2003)

PCT

(10) International Publication Number
WO 03/058230 A1

(51) International Patent Classification⁷: **G01N 27/447**,
G06K 9/64

(21) International Application Number: PCT/SE03/00029

(22) International Filing Date: 10 January 2003 (10.01.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
0200072-7 11 January 2002 (11.01.2002) SE
60/350,252 15 January 2002 (15.01.2002) US

(71) Applicant (for all designated States except US): **LUDESI AB** [SE/SE]; Växthuset Idéon, Ole Römers väg 12, S-223 70 Lund (SE).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **HEYDEN, Anders** [SE/SE]; Skogslyckevägen 9, S-240 10 Dalby

(SE). **MALMSTRÖM, Lars** [SE/US]; 4203 11th Avenue NE, Seattle, WA 98105 (US). **MALMSTRÖM, Johan** [SE/SE]; Vapenkroken 19, S-226 47 Lund (SE). **FORSSTRÖM-OLSSON, Ola** [SE/SE]; Trastvägen 3, S-227 31 Lund (SE). **BERGLUND, Magnus** [SE/SE]; Råbyvägen 15 H:24, S-224 57 Lund (SE).


(74) Agent: **STRÖM & GULLIKSSON IP AB**; Sjöporten 4, S-417 64 Göteborg (SE).

(81) Designated States (national): AE, AG, AL, AM, AT (utility model), AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ (utility model), CZ, DE (utility model), DE, DK (utility model), DK, DM, DZ, EC, EE (utility model), EE, ES, FI (utility model), FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK (utility model), SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),

[Continued on next page]

(54) Title: METHOD AND COMPUTER PROGRAM FOR DIGITAL IMAGE PROCESSING FOR TWO-DIMENSIONAL ELECTROPHORESIS



(57) Abstract: Method for processing digital image data for a two-dimensional array of sample substance spots and marker substance spots in an electrophoresis gel by using landmark substances having predefined properties, comprising the steps of: generating an ideal image represented by co-ordinate data corresponding to ideal positions of the marker substance spots in said array dependent on electrophoresis conditions; generating a marker image represented by co-ordinate data corresponding to detected positions of said marker substances spots in the array; determining a mathematical relation between the ideal image and the marker image, such that the co-ordinate data of said images are mapped onto each other; generating a sample image represented by a sample image data set corresponding to detected signal values in the gel; and normalising the sample image by transforming it dependent on said mathematical relation.

WO 03/058230 A1



Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,
ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, SE, SI,
SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN,
GQ, GW, ML, MR, NE, SN, TD, TG).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:

— *with international search report*

TITLE

Method and computer program for digital image processing
for two-dimensional electrophoresis.

5 DESCRIPTION**FIELD OF THE INVENTION**

The present invention relates to methods and devices for digital image processing of
biological sample separations. More specifically it relates to techniques for processing
10 digital image data for a two-dimensional array of sample substance spots and marker
substance spots in an electrophoresis gel by image normalisation.

BACKGROUND OF THE INVENTION

In a cell obtainable from e.g. a cell culture or tissue sample an existing pool of
15 proteins, a proteome, exists as a part of biological processes and functions. In many
different clinical, diagnostical and analytical situations it is desirable to gain knowledge
about the identity and amount of a protein or a group of proteins at a certain point in
time, and also of certain changes over time. Certain biological processes are defined
by changes in morphology and physiology due to changes in the expression, i.e. the
20 protein level, of particular genes. Also, developmental stages of cells can be defined
and monitored by their global pattern of gene expression and the progressive changes
that occur over time of particular genes or groups of proteins. Even more, as a
response to treatment of cells with chemical factors, e.g. drugs, hormones, nutrient
factors, environmental factors and other growth condition factors, specific proteins of
25 groups of proteins can change their expression and as such allow for monitoring or
identifying a response or treatment. Information of this type can be used to e.g.
detect, identify and classify tumours in terms of malignancy, evaluation of therapies,
adjustment of therapies as well as diagnosis and prognosis. Also, changes in proteins
due to mutations, cleavage, phosphorylation or glycosylation can be obtained. Further
30 identification of unknown proteins can e.g. be done by mass-spectrometry of
unidentified sample protein spots on the gel.

A general method used for detecting, identifying, monitoring and quantifying the
compositions of complex biological mixtures is two-dimensional gel electrophoresis. In
35 such a method the separation performed in two dimensions enables detection and
identification of a large number of components that would not be separable and
distinguishable in a one-dimensional separation, such as a linear separation. A
frequently used method for monitoring the protein expression by 2D (two-

dimensional) gel electrophoresis comprises the feature of analysing a set of multiple gels in one run.

A typical prior art method is detection and identification of sample spots in a 2D polyacrylamide gel. By using large gels, the number of proteins to be detected and identified can be several hundred up to about 10 000 in one gel. Each spot is detected by means of a signal derived from the individual spot. In a typical gel size of 24x18 cm, several thousands of sample protein spots are detected. Normally, about 10% of the total number of sample spots need to be selected as so-called landmarks. After a separation process has been performed, the spatial relation between these landmarks, or markers, and the sample spots is measured and used for the purpose of identification of the sample substances, in a manner well known to the skilled person. This further involves a few hundred manually selected landmarks in each gel. The process of detection, identification and analysis of the separate components in a two-dimensional electrophoresis gel is a complex and difficult task, and often involves tedious and time consuming manual steps demanding months of experience to perform. Several attempts have been made to develop means and methods to simplify, standardize and automise the procedure as described in Smilansky et al., 2001, *Electrophoresis* 22: 1616-1626; Thompson et al., 1998, in 20th Annual International Conference of the IEEE Engineering in Medicine and Biology Society, Vol. 20: 1060-1063; Wanatabe, et al., 1998, in 20th Annual International Conference of the IEEE Engineering in Medicine and Biology Society, Vol. 20:804-808.

The manner in which the sample protein spots are distributed across the two-dimensional gel-electrophoresis depend on the separation parameters used in the first and second dimension in the two-dimensional electrophoresis procedure. Two parameters commonly used are isoelectric point and molecular size (Gorg et al., 2000, *Electrophoresis* 21:1037-1053). Furthermore, various ways of obtaining detectable signals from the spots have been used, such as post-gel colouring techniques, e.g. silver staining as described in Sinha et al., 2001, *Proteomics* 1:853-840; Shevchenko et al., 1996, *Anal. Chem.* 68:850-858. Other techniques that are used include optical density, radioactive emission, fluorescence emission, and colorimetric signals (Pavon et al., 1999, *J Interferone Cytokine Res.* 19:589-599; Steinberg et al., 2001, *Proteomics*, 1:841-855; Herich et al., 2001, *Biotechniques*, 31:146-149; Kemper et al., 2001, *Electrophoresis*, 22:970-976; Lauber et al., 2001, *Electrophoresis* 22:919-932; Berggren et al., 2000, *Electrophoresis* 21:2509-2521; Steinberg et al., 2000, *Electrophoresis* 21:486-496). Detection of the spots is commonly achieved by the use of imaging devices that convert the detected signals into digital data and store the data as information on computer storage media.

One of the key features in identifying the sample spots is the assignment and use of reference spots known as "landmarks". The landmarks are actual protein spots that are manually selected by the user, i.e. manual landmarking. Computer software is further used for processing the manually selected spots in order to automatically
5 detect and identify the same spots in all of the member gels in one matchset. These user-selected landmarks are preferably relatively few in number compared to the total number of sample spots in an individual electropherogram. The selection criteria of the manual landmarks are that the spots should be well-resolved, that they are well isolated from other spots, and that they appear in all the gels of the matchset.
10 The number of spots to be assigned as landmarks must be large enough that all of the remaining protein spots among the various gels will be successfully matched by the automatic processing. The function of the landmarks is to serve as guideposts in the gel-to-gel comparison, thereby aiming at reducing and compensating differences and distortions among the member gels in the matchset to assure that there will be a
15 proper correspondence of protein spots among different gels in the matchset.

Further, by using known sample proteins manually chosen as landmarks in the 2-DE one has to consider only proteins that exists in all gels in one matchset. Such protein must exist in a relatively large amount to be readily repeatable and detectable in all of
20 the gels. Due to this, the spots chosen as protein landmarks are often large and blob-like. This gives less defined landmarks that are difficult to position accurately, i.e. to find the exact centre of the landmark, which is a source of inaccuracy on the analysis process of the sample protein spots.

25 The process of selecting and marking spots to be used as landmarks is slow and tedious, and is one of the limiting factors in two-dimensional gel electrophoresis analysis. Normally, since about 10% of the total number of protein spots needs to be selected as protein landmarks to make the image analysis algorithm work correctly, several hours must be used for each run to pick said landmarks manually. Also, in
30 addition to assigning the above described selection criteria for manually chosen landmarks, the time involved in making the selections and making the spots adds to the cost and time involved in performing the analysis. Even further, the level of user involvement raises question regarding reproducibility and reliability.
35 Being a generally known and widely used technique, the state of the art comprises several disclosures relating to two-dimensional electrophoresis.

US 5 139 630 teaches a method for detecting and identifying protein species in a sample by capillary zone electrophoresis by the addition of at least two external

markers, one being an ionic species and one being a neutral charged species. This method is only applicable for capillary electrophoresis, i.e. where the separation is in one dimension, here disclosed for charge densities, and not applicable for a separation using more than one dimension as in e.g. a two-dimensional gel electrophoresis.

5

WO 01/07920 discloses a method for automated landmarking for two-dimensional gel electrophoresis by the addition of marker proteins to the sample proteins. However, the use of proteins as external landmarks has several disadvantages, such as high production costs and short shelf life of the final protein product. Further, the use of protein landmarks, means that special means have to be taken to make such proteins visualized in contrast to proteins present in a sample material.

In the light of the aforementioned problems it is thus an object of the invention to provide means and methods for reducing time and cost relating to the process of electrophoresis. An aspect of this object is to increase the reproducibility and reliability of two-dimensional gel electrophoresis used for separation, detection, identification and quantification of proteins, and to provide a solution overcoming the problems associated with the prior art means and methods.

20 SUMMARY OF THE INVENTION

In order to fulfil the objects above, the present invention provides means and methods for using detected signals from landmarks, herein also called markers, having known properties in order to transform a detected 2D gel image to a form in which it is comparable to other images of 2D gels. The landmarks may be selected from the sample, provided it is known that they will be present. Alternatively, a set of so-called external landmarks is used, which external landmarks have been added to the sample beforehand. The term external is simply used to point out that the landmark substances used are not selected from the sample substances to be determined, but are included in addition to the sample substances to be determined and quantified, prior to the electrophoresis process. Hence, these external landmarks are subjected to the same and separation process as the samples substances to be determined. Preferably, such external landmarks are artificially created, such that their properties will give rise to a desired spatial distribution of landmark spots in the gel after an electrophoresis run.

35

According to a first aspect of the invention it relates method for processing digital image data for two-dimensional arrays of sample substance spots and marker substance spots in a plurality of electrophoresis gels by using marker substances having predefined properties, comprising the steps of:

- generating marker images represented by marker image data sets comprising coordinate data and signal values corresponding to detected positions and signal values of said marker substance spots in said arrays;
- processing said marker images to determine a mathematical relation between said marker signals in said marker images such that said respective signals are mapped on each other;
- generating sample images represented by sample image data sets comprising coordinate data and signal values corresponding to detected positions and signal values of said sample substance spots in said arrays;
- 10 - transforming said sample image signals according to said mathematical relation

In a preferred embodiment the invention is a method for the detection, matching and quantification of sample substances in a plurality of electrophoresis gels by using external marker substances having predefined properties, the method comprising the steps of:

- 15 - combining each of said gels with said sample substances and a plurality of said external marker substances each having a known identity and known characteristics that affect its migration in two-dimensional electrophoresis, which said external marker substances are selected such that they are distinguishable from said sample substances;
- 20 - performing two-dimensional electrophoresis on said gels thus combined with said sample substances and said external marker substances to form a two-dimensional array, each array including said external marker substance spots corresponding to said external marker substances and sample spots corresponding to said sample substances;
- 25 - scanning each array to form a first image of signals corresponding to said external marker substance spots and a second image of signals corresponding to said sample substance spots, the signals of said first image being distinguishable from those of said second image;
- 30 - processing said first image together with the known identity and known characteristics of said external marker to determine a mathematical relation between said first image signals and signals representing said known identity and said known characteristics of said external marker substances such that said respective signals are mapped on each other;
- 35 - transforming said second image signals dependent on said mathematical relation such that the external marker substance spots are positioned as external marker reference spots on the co-ordinates in the two-dimensional array that correspond to their properties in said electrophoresis gel;

- determining the properties of said sample spots dependent on said external marker reference spots in said transformed second image.

In another preferred embodiment the invention is a method for analysing samples

5 substances by comparison between a first electrophoresis gel and a second electrophoresis gel by using external marker substances having predefined properties, the method comprising the steps of:

- combining each of said gels with said sample substances and a plurality of said external marker substances each having a known identity and known characteristics
- 10 that affect its migration in two-dimensional electrophoresis, which said external marker substances are selected such that they are distinguishable from said sample substances;
- performing two-dimensional electrophoresis on said gels thus combined with said sample substances and said external marker substances to form a two-dimensional
- 15 array, each array including said external marker substance spots corresponding to said external marker substances and sample spots corresponding to said sample substances;
- scanning each array to form a marker image of signals corresponding to said external marker substance spots and a sample image of signals corresponding to said sample
- 20 substance spots, the signals of said marker image being distinguishable from those of said sample image;
- determining a mathematical relation between the signals of the respective marker image of said sample gels, such that the signals corresponding to spots of the same marker substance in the marker images of the first and the second electrophoresis gel
- 25 are mapped on each other;
- transforming the sample image of the first gel dependent on said mathematical relation, such that the sample images of both gels relate to the same external marker substance positions; and
- determining differences between the two electrophoresis gels by directly comparing
- 30 the transformed sample image of the first gel with the sample image of the second gel.

In a further preferred embodiment the invention is a method for analysing samples substances by comparison between a first electrophoresis sample gel and a second

35 electrophoresis gel by using external marker substances having predefined properties, the method comprising the steps of:

- combining each of said sample gels with a common set of external marker substances each having known properties affecting its migration in two-dimensional electrophoresis;

- performing two-dimensional electrophoresis on each of said sample gels thus combined with said external marker substances to form a two-dimensional array, each array including external marker substance spots corresponding to said external marker substances and sample spots corresponding to said sample substances;
- 5 -scanning each array to form a marker image of signals corresponding to said external marker substance spots and a sample image of signals corresponding to said sample substances spots, the signals of said marker image being distinguishable from those of said sample image;
- applying a mathematical relation between the signals of the respective marker image
- 10 of said sample gels, such that the signals corresponding to spots of the same marker substance in the marker images of the first and the second electrophoresis gel are mapped on each other;
- transforming the sample image of the first gel dependent on said mathematical relation, such that the sample images of both gels relate to the same marker
- 15 substance positions; and
- determining differences between the two electrophoresis gels by directly comparing the transformed sample image of the first gel with the sample image of the second gel.
- 20 In another preferred embodiment the invention is a method for processing digital image data for a two-dimensional array of sample substance spots and landmark substance spots in an electrophoresis gel by using landmark substances having predefined properties, comprising the steps of:
- defining ideal image data comprising co-ordinate data corresponding to ideal
- 25 positions of the marker substance spots in said array dependent on electrophoresis conditions;
- generating a marker image represented by marker image data comprising co-ordinate data corresponding to detected positions of said marker substances spots in the array;
- 30 - determining a mathematical relation between the ideal image data and the marker image data, such that the co-ordinate data of said images are mapped onto each other;
- generating a sample image represented by a sample image data set corresponding to detected signal values in the gel;
- 35 - transforming said sample image according to said mathematical relation.

In still another preferred embodiment the invention is a method for processing digital image data for two-dimensional arrays of sample substance spots and marker

substance spots in a plurality of electrophoresis gels by using external marker substances having predefined properties, the method comprising the steps of:

- generating digital images represented by marker image data sets and sample image data sets comprising coordinate data and signal values corresponding to detected positions and signal values of said marker substance spots and sample substance spots in the arrays.
- processing each said digital image to extract the marker substance data sets comprising coordinate data and signal values corresponding to detected positions and signal values of said marker substance spots in the arrays.
- processing said digital images to determine a mathematical relation between the marker signals in said digital images such that said respective signals are mapped on each other.
- generating sample images represented by sample image data sets comprising coordinate data and signal values corresponding to detected positions and signal values of said sample substance spots in the arrays
- transforming said sample image signals according to said mathematical relation

In still another preferred embodiment the electrophoresis gels contain a plurality of sets of, in relation to each other distinguishable, sample substances such that a plurality of sample images for each electrophoresis gel is acquirable.

In still another preferred embodiment the step of generating said sample image comprises the step of scanning the array to form a pixel image, and wherein the step of transforming the sample image data signals comprises the step of transforming every pixel of said sample image into a transformed image, dependent on said mathematical relation.

In still another preferred embodiment said array comprises two different marker substances having different properties, from which different properties co-ordinate data relating to ideal marker spot positions differing in at least one dimension for given electrophoreses operating conditions can be calculated.

In still another preferred embodiment said array comprises a plurality of different marker substances having different properties, from which different properties co-ordinate data relating to ideal marker spot positions differing in two dimension for given electrophoreses operating conditions can be calculated.

In still another preferred embodiment, dependent on the electrophoreses operating conditions, a set of marker substances is selected, comprising said plurality of different

marker substances, dependent on their corresponding co-ordinates of in the ideal image data.

- In still another preferred embodiment the step of normalising the sample image
- 5 comprises the process steps of:
- selecting a first pixel in the image plane defined by said ideal image data;
 - mapping said first pixel to the sample image;
 - reading the detected signal value for the mapped first pixel;
 - assigning said detected signal value to said first pixel in the image plane of the ideal
- 10 image data; and
- repeating these process steps for each pixel in the image plane.

- In still another preferred embodiment the step of reading the detected signal value for the mapped first pixel comprises the step of:
- 15 - establishing a detected signal value for the mapped first pixel dependent on the signal value of at least one pixel in the sample image adjacent the mapped first pixel.

- In still another preferred embodiment the step of normalising the sample image comprises the process steps of:
- 20 - selecting a first pixel in the sample image;
- reading the detected signal value for said first pixel;
 - mapping said first pixel to the image plane defined by said ideal image data;
 - assigning said detected signal value to the mapped first pixel in the image plane of the ideal image data; and
- 25 - repeating these process steps for each pixel in the sample image.

- In still another preferred embodiment the step of normalising the sample image comprises the process steps of:
- selecting a first pixel in the image plane defined by said ideal image data;
- 30 - reading the detected signal value for the mapped first pixel;
- mapping said first pixel to the sample image;
 - assigning said detected signal value to said first pixel in the image plane of the ideal image data; and
 - repeating these process steps for pixels in the image plane defining an object
- 35 consisting of sample substance spots and/or marker substance spots.

In still another preferred embodiment the foregoing further comprising the steps of:

- determining the signal value for a first pixel in the ideal image plane dependent on the signal value of at least one mapped pixel in the ideal image plane adjacent said

first pixel in the ideal image plane; and

- repeating this determination process for each pixel in the ideal image plane.

5 In still another preferred embodiment the marker substances are non-protein compounds.

In still another preferred embodiment said marker substance is an compound comprising a least a functional unit.

10 In still another preferred embodiment said marker substance is an compound comprising a least a monomer unit and a functional unit.

In still another preferred embodiment the detection of the landmark spots is done by monitoring the shapes of the landmark spots, both in two and three dimensions.
15

In still another preferred embodiment the detection of the landmark spots is done by monitoring the pattern(-s) of the landmark spots in the gel.

20 In still another preferred embodiment the detection of the landmark spots is done by monitoring a combination of both shapes and pattern(-s) of the landmark spots in the gel.

In still another preferred embodiment the detection of the landmark spots is done by monitoring the positions of the landmark spots in the gel.
25

In still another preferred embodiment the detection of the landmark spots is done by monitoring a combination of both shapes and positions of the landmark spots in the gel.

30 In still another preferred embodiment the detection of the landmark spots is done by monitoring a combination of both positions and pattern(-s) of the landmark spots in the gel.

35 In still another preferred embodiment the detection of the landmark spots is done by monitoring a combination of shapes, pattern(-s) and positions of the landmarks spots in the gel.

Another aspect of the invention encompasses a computer program product for use in a computer system, comprising computer program code means for executing the

computer system to process digital image data for a two-dimensional array of sample substance spots and marker substance spots in an electrophoresis gel, by performing the steps of:

- accessing coordinate data for a marker image, relating to detected positions of marker spots of a predetermined substance in the array, dependent on electrophoresis operating conditions;
- accessing coordinate data for another marker image, relating to detected positions of marker spots of said predetermined substance in the array;
- determining a mathematical relation between said marker images, such that the coordinate data of said images are mapped onto each other;
- generating a sample image represented by a sample image data set corresponding to detected signals in the gel;
- transforming the sample image by transforming it dependent on said mathematical relation.

15

In a preferred embodiment of the computer program product it further comprises computer program code means for executing the computer system to perform the steps of any of the claims 1 – 27.

- 20 Needless to say, this method can be used to compare plural gels, two by two. Since the markers are selected and have known properties, this transformation and subsequent comparison can be performed completely automatic for two or more gels, saving hours of work which as such constitutes a potential source of manual errors.

25 BRIEF DESCRIPTION OF THE DRAWINGS

The features of the present invention will be described in more detail below by means of preferred embodiments and examples, with reference being made to the appended drawings, in which

- Fig. 1 schematically illustrates a grid of co-ordinates relating to ideal positions of landmark spots in an electrophoresis gel for given electrophoresis conditions, according to an embodiment of the invention;
- Fig. 2 schematically illustrates a grid of co-ordinates relating to the detected positions of landmark spots in an electrophoresis gel for said given electrophoresis conditions, according to an embodiment of the invention;
- Fig. 3 schematically illustrates an image comprising the sample spots of the same electrophoresis gel, according to an embodiment of the invention; and
- Fig. 4 schematically illustrates a normalised image of the sample image in Fig. 3, according to an embodiment of the invention.

DETAILED DESCRIPTION OF PREFERRED EMBODIMENTS

As revealed above, the present invention relates to the method of using external markers in a gel electrophoresis process for normalising images from 2-D gels, making it possible to match sample spots between different images from 2-D gels, and to
5 quantify sample spots in images from 2-D gels, in a more effective way than with the prior art techniques.

Once a electrophoresis separation process has been performed on a gel comprising sample substances and landmark substances, these substances will be gathered in
10 spots dependent on their properties, wherein each spot, or the centre thereof, corresponds to a certain parameter value pair in the two dimensions. The resulting pattern of spots will hence form a 2D array of more or less discrete spots. A suitable technique for capturing an image of this pattern is subsequently used, such that signals from the spots in the array are detected. Preferably the image is captured by
15 scanning, but may also be captured by a single shot. The position of the landmark spots is then determined from the captured image. By using a digital scanner, the capturing of the image and the determination of the landmark spot positions may be performed in essentially the same step. From a single shot image, the spot positions may be determined by subsequent scanning of that image.

20 In order to detect the landmark spots, i.e. the positions of the landmark spots in the captured image, it is advantageous if the landmark substances are easily distinguishable from the sample substances. As described below this can be achieved in various ways. A suitable algorithm preferably is used to determine the co-ordinates
25 for the centre of the spots for preferably all landmark spots in the gel. A data set of pairs of co-ordinates is thus formed, a detected landmark data set, representing signals in a detected image in an actual electrophoresis case. Each co-ordinate pair of the detected landmark image refers to a certain parameter value pair in the two dimensions of the 2D electrophoresis. One example of a landmark image, wherein the
30 detected positions for the landmark spots are indicated, is shown in Fig. 2.

Furthermore, a sample image is formed by capturing an image of the gel in which the sample spots are detected. As a person skilled in the art will realise, the landmark image and the sample image may be derived or formed from the same captured
35 image, or from successive captured images. The sample image is digitally represented by a sample image data set comprising a signal value for each pixel in the captured sample image, or global image. This global image may or may not include the landmarks. Preferably, said signal value is expressed as a level of magnitude in a scale, such as a grey scale, relating to the exposure of the image in that particular

pixel. An example of a sample image of a separated electrophoresis gel is shown in Fig. 3, corresponding to the landmark image of Fig.2.

For different reasons, such as inconsistencies in the gel, the landmark substances in an actual electrophoresis run will rarely be located as would be expected from their known properties and the chosen electrophoresis conditions. This is one of the reasons why simple direct comparison between two electrophoresis cases is not always reliable, since this uncertainty naturally is equally valid for the sample substances.

According to the invention, this problem is overcome by transforming the global image such that the external landmarks are positioned in the co-ordinates to which their properties in the separation processes correspond. This way, two or more electrophoresis gels ran under the same conditions may be independently transformed into a reference format, such that they may be compared to each other. The transformation feature of the invention is based on usage of known landmarks. One feature of using landmarks selected from substances of known properties is that when the conditions of the separation process of the electrophoresis are known, also the expected positions which these marker substances would ideally assume in the gel are known, or can be derived. By said conditions is here meant for instance the type, e.g. isoelectric point and molecular size, and range of parameters used to separate the samples in the gel, and the type of gel used. Consequently, once a set of landmark substances is chosen and certain electrophoresis conditions are selected, a pattern of discrete co-ordinates corresponding to the positions those landmark substances would assume, based upon their properties, can be derived. Accordingly, a data set of pairs of reference co-ordinates is thus formed, here denoted a reference landmark data set, representing signals in a reference image or ideal image relating to an ideal electrophoresis case. Each co-ordinate pair of the reference image refers to a certain parameter value pair in the two dimensions of the 2D electrophoresis. An example of an ideal marker image, corresponding to the landmark image derived from the detected landmarks as shown in Fig. 2, is illustrated in Fig. 1. By comparison between these two figures it will be obvious that the positions of the corresponding markers do not coincide perfectly.

In order to be able to perform the aforementioned transformation, a mathematical relation between the reference landmark data set and the detected landmark data set is determined, such that the co-ordinates of the landmarks, or markers, in the two images represented by said data sets, i.e. the reference image and the detected landmark image, are mapped onto each other. The mathematical relation for this mapping is calculated from the position differences between corresponding co-ordinate

pairs in the respective sets, but at the same time the mathematical relation is continuous for the entire reference image.

Each pixel of the transformed image is then created by collecting the value for the corresponding pixel in the detected global image according to the following basic procedure. A first pixel in the image plane of the reference image is mapped by said mathematical relation into the image plane of the detected global image. If the global image is distorted compared to what would have been expected under the present conditions, the co-ordinates of the mapped pixel will not be the same as the original pixel in the reference image plane. Once the mapped pixel co-ordinates have been calculated, the signal value of that co-ordinate is read in the sample image data set, and that signal value is thereafter assigned to said first pixel in the reference image plane. Each part of the reference image plane is then built up pixel by pixel to form a complete transformed image of the detected global image.

Consequently, the entire detected image of samples is transformed by this mapping. The detected image is then globally transformed. An example of a such a globally transformed, normalised, image is illustrated in Fig. 4. In fact, the image in Fig. 4 is transformed from the detected sample image of Fig. 3, using a mathematical relation derived from the relation between the ideal and detected landmark images of Figs 1 and 2, respectively, in accordance with an embodiment of the invention. All electrophoresis test items separated by this specific type of gel and strip, and having the corresponding set of landmarks, will in this globally transformed format have their landmarks placed on exactly the same positions or co-ordinates. A specific example of determining a mathematical relation for mapping the landmark images onto each other is described further below.

In a preferred embodiment of the invention, external landmarks are used. Preferably these external landmarks are artificial molecules which are not proteins, as disclosed in the related patent application SE 0103103-8, which is hereby enclosed by way of reference.

Several technical effects are obtained by the invention. The analysis of the detected image is automatised in a higher degree than in the prior art solutions. By adding external knowledge, i.e. substances of known properties, the time-consuming manual placing of landmarks in the image, which is also a potential source of errors, in order to obtain a match with another image, is eliminated. Instead, each image is independently processed into a format in which it is comparable with any other processed image carrying the same landmarks.

Using selected artificial landmarks further brings about the effect that landmark substances can be selected such that they form a desired pattern over the image, e.g. with substantially equal distance between each neighbouring landmark spots, resulting in a more even accuracy over the entire image and a more accurate transformation.

- 5 The proteins functioning as landmarks in the prior art are spatially rather undefined and differing from time to time, which results in an uncertainty in the positioning in the landmarks from a spot. Detection of the artificial landmarks is more secure since the same amount of a certain landmark substance is always selected, wherein the spot will essentially always look the same. Therefore, the algorithm used will determine the
- 10 co-ordinates in essentially the same way each time, rendering a more accurate positioning.

- According to an embodiment of the invention, the marker compounds suitable for gel electrophoresis are added externally, and are not chosen from the samples, as
- 15 revealed above. The marker compound may be a polymer or it may be selected from the group consisting of glycoconjugates, carbopeptoides, polynucleotides, proteoglycans, fullerenes, carbohydrates and mixtures thereof.

- In specific embodiments, the marker compound is characterised by a pI of about 2-12.
- 20 In still further embodiments, it is characterised by a pI of about 3-10.

- Further embodiments include marker compound characterised by a Mw of about $5 \cdot 10^6$ Da. In still even further embodiments, the Mw may be of about 10^3 - 10^5 Da, 5-1000 Da, 5-600 Da, 5-250 Da or an otherwise suitable interval of molecular size due to the
- 25 size of the samples to be separated and detected. Specific embodiments comprise marker compounds characterised by a pI of about 1-12 and by a Mw of about 100 - 10^6 .

- In one embodiment the marker compound is a dendrimer. Dendrimers are built up from different structural building blocks, some that may include branching points to
- 30 achieve a tree like structure characteristic for dendrimers. The different building blocks are coupled together to achieve said treelike structure.

- The dendrimers offer two important features when used as marker molecules, namely a) the size can be easily modified by adding more layers and b) the feature of the
- 35 dendrimeric compounds can be modified by adding different functional groups to the layers. Since the individual building blocks may be composed of repeatable units, the dendrimer molecule may be built up from only a few numbers of coupling steps, which is economically and technically advantageous.

According to the invention, the dendrimer may comprise at least one monomer, at least one functional group and optionally at least one core as building blocks. The dendrimer may be built up from separate building blocks as shown in figure 2 in the patent application application SE 0103103-8 referred to above. Said dendrimers may
5 be built up either by a divergent strategy or by a convergent strategy as known in the art of dendrimer synthesis.

In one embodiment, the dendrimer to be used as external landmarks according to the invention is synthesised according to the divergent strategy.

10

The dendrimer may be represented by the general formula

$(\text{core})_n (\text{monomer}_{1\dots o})_x (\text{functional group}_{1\dots p})$

- 15 wherein n is an integer from 0-5 representing number of different co-existing optional cores,
wherein o is an integer from 2-1000 representing number of different monomer building blocks within the monomer distributed over x layers,
wherein x is an integer from 1-20 representing number of layers, and
20 wherein p is an integer from 1-20 representing the number of different functional groups within one functional group building block.

Other suitable dendrimers to be used as landmarks according to the invention are commercially available dendrimers. Though, such dendrimers lack at least one
25 functional group according to the invention. Such a functional group may then, of course, be coupled onto the commercially available dendrimers using techniques known to the skilled man in the art. Examples of, but not limited to, commercially available dendrimers that may be used according to the invention are Astramol™ (DSM Agro, The Netherlands) and Starbust® (Aldrich)

30

In specific embodiments of the invention, synthetic amino acid dendrimers will be used. In still a specific embodiment, a diamin or a triamin is used as a core, diaminobenzoic acid as a monomer and aspartic acid as a functional group. By introducing different numbers of diaminobenzoic acid as a monomer a huge range of
35 molecular masses may be achieved as exemplified in the table below.

Molecular size of dendrimers made of a diamin as core building block, diaminobenzoic acid as a monomer (mon) and aspartic acid as a functional group.

mon	Molecular size
0	290
1	788
2	1785
3	3779
4	7767
5	15743
6	31694
7	63597

The dendrimer may comprise at least one core. According to specific embodiments, the core may include divalent, trivalent, tetravalent, multivalent cores and mixtures thereof. According to the invention, the at least one core may be selected from the group consisting of the formulas in figure 3 of SE 0103103-8, and mixtures thereof.

In one embodiment, the core may be a diamine where $n=2$ or a triamine where $n=1$.

The core may contain further branching units, allowing the treelike structure characteristic of the dendrimer to form.

An example of a dendrimer using diaminoethane as the core is shown in figure 4 of SE 0103103-8.

The dendrimer also comprises at least one monomer. The monomer may include further branching possibilities to the dendrimer molecule to achieve the treelike structure characteristic of the dendrimer. Due to the numbers of branching possibilities, the monomer may be monovalent, i.e., to elongate without branching, divalent, trivalent, tetravalent, multivalent or mixtures thereof. Examples of such monomers with monovalent and divalent branching units are shown in figure 5 of SE 0103103-8.

Specific embodiments use amid bondings between the different monomers.

In still a further embodiment, the at least one monomer may be 3,5- diaminobenzoic acid, as shown in figure 4 of SE 0103103-8.

The number of monomers will contribute to the final molecular size of the dendrimer.

- 5 According to specific embodiments, using 3,5- diaminobenzoic acid as monomer the monomer may be in a number of 1-10.

- 10 The dendrimer may also contain a functional group according to the invention. The at least one functional group will to the dendrimer ad known characteristics. An example of known characteristics is, e.g. a desired net charge to the molecule.

- 15 In specific embodiments, at least one functional group may be added to the free ends generated in the coupling step. Due to the addition of the at least one functional group, the landmark will according to the invention be able to position in the gel if the gel parameters used for separation are selected so as to enable separation of the marker compound characteristics.

- 20 According to different embodiments the at least one functional group may be selected from the group of functional groups shown in figure 6, and zwitterions, anionic or cationic, oligopeptides, alcohols, tiols, carboxy acids, amines; fluorochromes, such as fluorescamine, isotopes and mixtures thereof .

- 25 In a specific embodiment, the fluorescamine used is the commercially available Fluram® available from Molecular Probes, U.K.

In still further specific embodiments, the at least one functional group is selected from the group consisting of an amino acid such as aspartic acid, glutamic acid.

- 30 According to the invention, the marker compound has known characteristics affecting its migration in a gel during gel electrophoresis so as to position the marker compound in said gel. Such characteristics may, of course, be included by the addition of a functional group to the dendrimer. Even further, it may reflect the molecular size of the marker compound.

- 35 By selecting landmarks with chosen characteristic, such as, e.g. pI and molecular size values, the external added landmarks may position in a desired way over the gel. Such information about characteristics of the external markers may be used for further analysis of unknown samples, such as unknown proteins.

According to the invention, a set of marker substances may form at least two marker spots in a gel after an electrophoresis run. As such, these spots will appear in different areas in the gel, due to the known characteristics of the marker compounds that form said spots, separated in at least one dimension. The number of marker spots may differ. This is due to the large number of different types of gels to be used in the gel electrophoresis step. Another factor that may affect the number of markers needed are the number of sample spots on the gel, which is obvious for the skilled man in the art of gel electrophoresis and separation of samples such as e.g., protein samples. Other factors that affect the number of spots needed are the number of separation dimensions. The invention is applicable to electrophoresis separation in at least one dimension and preferably two, but may be applied in separation in more than two dimensions. The number of marker spots needed may therefore be, such as about 0-50% of the number of sample spots, preferably 1-20%, e.g. 1-10% of the number of sample spots. Specific embodiments of the invention may use marker spots, wherein the at least two marker spots may be from about 2-1000 marker spots per said gel. In still further embodiments, the at least two marker spots may be from about 2-500, 10-250, 10-100, or about 20-40 marker spots per gel. In an embodiment of a two dimensional gel, e.g. a polyacrylamid gel, in a size of about 24x18 cm, the number of marker spots needed may be about 9-40, e.g. 9-16 marker spots.

The grid formed by the distributed marker spots in the gel may be spatially even, but the marker set may also be selected such that the marker spots will appear unevenly distributed for various reasons. One such reason may be that is known or suspected beforehand that certain sample substances will be present in the gel and will gather in a specific region of the gel. It may then be desirable to select markers which will equally be gathered in the vicinity of this region, in order to have a sufficient amount of landmark readings in this region in order to improve the sample quantification accuracy.

The marker spots appearing in a gel will contain different number of marker compounds per marker spot. However, the amount of marker compounds should be enough to allow a clear and concise detection of the marker spot on the gel. This is, of course, dependent on how the sample spots are detected, equipment and/or gel resolution.

According to specific embodiments of the invention, at least two marker compounds are used forming at least two marker spots which may position in the gel at ideal positions. As used herein, the word ideal is intended to mean ideal due to empirical information, such as experimental data, or from theoretical information, such as

chemical and/or physical data characterising the marker compounds used. Such compounds may be designed to be dependent upon e.g. pI and molecular size for their positioning. Of course the marker compounds may be designed in different ways, as obvious to the skilled man in the art, to depend upon other characteristics for

5 separation according to other dimensions than pI and molecular size.

The set of external landmarks may in specific embodiments comprise at least two marker compounds forming at least two spots, wherein the at least two marker compounds are characterised by a pI of about 1-12, such as about 3-10. In still further embodiments, the at least two marker compounds may be characterised by a Mw of

10 about $100-10^6$, such as about 10^3-10^5 . Specific embodiments of the invention may include two marker compounds characterised by a pI of about 1-12 and a Mw of about $100-10^6$.

The application of a set of marker or landmark substances or compounds in a gel may

15 include applying the set in the form of application strips or mixing and applying the set together with the test samples, or applying the set at the time of casting of the gel.

When an electrophoresis separation has been made and the sample and marker substances have been positioned into spots in the gel, information about the position

20 of each separated marker compound needs to be collected and stored. This information may be collected using any of the determination processes selected from a group comprising visual light, UV, IR, multispectral imaging, isotope labelling, colouring techniques such as silver staining, Comassie staining, and fluorescence techniques. The external marker substances are preferably selected such that they are

25 distinguishable from the sample spots in the gel. This may be achieved by using marker substances having optical properties different from the optical properties of the sample spots, making it possible to detect the external markers in the gel. The marker spots are preferably detected by scanning the gel and picking up signals representing the positions of the spots using any of the techniques in the aforementioned group.

30 The scanning procedure results in a digitized image, which is stored in a data memory.

The stained gels, both containing separated landmarks and sample molecules, may be scanned in a scanner with dual detection possibility. With dual detection possibility, it is intended to mean that the scanner has the possibility to detect signals from

35 different staining techniques, such as silver staining, fluorescent staining, radioactivity, or any other staining method used. In one embodiment, the landmarks are detected in a separate image, the marker image, after a scanning step, enabling detection of the landmarks positions only. Without changing the position of the gel, the parameters of the scanning apparatus are changed, so as to enable a separate

scanning and detection of the separated sample molecules, e.g. the proteins, in order to register a sample image. The two gel images, one with the separated landmarks and one with the separated sample proteins, now collected in digitalized form, are subsequently used for the image analysis of the gel. The gel may also be scanned
5 once, detecting the sample molecules and the proteins in one image. This may be convenient when the same detection methodology is used for the sample molecules and the landmarks, but when the optical and/or the geometrical properties of the marker spots and the sample spots allow differentiation between them.

The marker image is used for extraction of the co-ordinates for the spots of external
10 markers in the image. This is done by standard techniques in mathematical imaging, and any of a number of methods could be used. The result is a file consisting of data representing the co-ordinates from the detected external markers in the gel.

In accordance with the invention, the properties of the external markers according to the two separation parameters are known. For the set of external markers added to
15 the sample prior to the electrophoresis a file of those properties has been established and stored in a file on a computer readable storage media, such as a hard drive, a CD-ROM or other data storage device. The differences between the known properties and the observed positions of the external markers in the gel are subsequently used to construct a mathematical relation mapping the one set of data onto the other. The
20 relation should due to obvious reasons be injective and continuous over the whole defined image area. This mathematical relation could be defined and/or determined in any of a number of ways. The result is a mathematical function mapping the existing, detected, image of the sample spots, or the sample spots plus the marker spots, onto another image, the "globally transformed image". Below, one example of an
25 embodiment for carrying out the invention is described with reference to the accompanying drawings.

A silver stained gel formed in an electrophoresis separation process is placed in a scanner and scanned in two different ways, or in a way that allows differentiating the
30 marker spots from the sample spots, in order to extract the co-ordinates for the spot positions of the selected marker substances. The co-ordinates could typically be determined using segmentation of the marker spots, e.g. by using Watershed algorithm. A modified Gaussian distribution model of the marker spots may further be used to locate the centre of gravity for the spots and use the projection onto the x-y
35 surface as the co-ordinates for the spots. The co-ordinate data thus extracted is stored in a file. The file of data for the set of detected spots of landmark substances used in the image, and the file of the properties of said landmark substances, are loaded into a computer carrying a computer program devised in accordance with the invention. The computer program now has access to the observed data and the "known" data

relating to the landmarks. The known data on file may be specifically stated in the format of parameter pairs relating to the separation process used, but may also be stored in a form from which this value pair may be calculated dependent on electrophoresis conditions.

5

The co-ordinates for the ideal landmark positions are defined and accessible in the computer program as vectors named P_x and P_y . The co-ordinates for the detected landmark positions are defined and accessible in the computer program as vectors V_x and V_y . The x and y relate to the x -coordinates and the y -coordinates of the respective positions.

10

Using the P_x and the P_y , all distances between the landmarks in the image plane of the sought normalised image are calculated and stored in a vector r .

A function $U(r) = r^2 * \log r^2$ is then calculated for all the r 's, and stored in a matrix K .

15 This matrix is thus a $n \times n$ matrix over the n landmarks in the following manner:

$$K = \begin{bmatrix} 0 & U(r_{12}) & \dots & U(r_{1n}) \\ U(r_{21}) & 0 & \dots & U(r_{2n}) \\ \dots & \dots & \dots & \dots \\ U(r_{n1}) & U(r_{n2}) & \dots & 0 \end{bmatrix}.$$

$$\text{A matrix } P \text{ is constructed: } P = \begin{bmatrix} 1 & x_1 & y_1 \\ \dots & \dots & \dots \\ 1 & x_n & y_n \end{bmatrix}, \text{ that is a } 3 \times n \text{ matrix: } [1 \ P_x \ P_y].$$

20 Then a matrix or operator L is constructed according to:

$$L = \begin{bmatrix} K & P \\ P^T & 0 \end{bmatrix}, (n+3) \times (n+3), \text{ where } P^T \text{ is the transpose of the } P \text{ matrix and } 0 \text{ is a } 3 \times 3 \text{ matrix of zeros.}$$

25 Let $V = (v_1, v_2, \dots, v_n)$ be any n -vector, and write $Y = (V \mid 0 \ 0 \ 0)^T$, a column vector of length $n+3$. A vector $W = (w_1, w_2, \dots, w_n)$ and coefficients a_1, a_x, a_y are then defined by the equation $L^{-1}Y = (W \mid a_1 \ a_x \ a_y)^T$. According to the invention the elements of $L^{-1}Y$ are subsequently used to define a function $f(x,y)$ everywhere in the plane:

30

$$f(x,y) = a_1 + a_x * x + a_y * y + \sum_{i=1}^n w_i U(|P_i - (x,y)|).$$

The function f is divided into two parts: a sum of functions $U(r)$ and an affine part.

- 5 Let $V = \begin{bmatrix} x_1' & x_2' & \dots & x_n' \\ y_1' & y_2' & \dots & y_n' \end{bmatrix}$ where each landmark homologous to (x_i, y_i) in another copy of \mathbf{R}^2 . Here, \mathbf{R} represents the real numbers, and consequently \mathbf{R}^2 represents the real number pairs in the plane.
- 10 The application of L^{-1} to the first column of V^T specifies the coefficients of 1, x , y , and the U 's for $f_x(x,y)$, the x -coordinate of the image of (x, y) ; the application of L^{-1} to the second column of V^T does the same for the y -coordinate $f_y(x,y)$. The resulting function $f(x,y) = [f_x(x,y), f_y(x,y)]$ is now vector-valued: it maps each point (x_i, y_i) to its homolog (x_i', y_i') . Furthermore, this function is the least bent of all such functions,
- 15 according to the measure I_f , integral quadratic variation over all \mathbf{R}^2 , computed separately for real and imaginary parts of f and summed. These vector-valued functions $f(x,y)$ are the thin-plate spline mappings used in this method. If the pairings of points between the sets is in accordance with biological homology, the function f models the comparison of biological forms as a *deformation*. The whole procedure is
- 20 obviously invariant under translation or rotation of either set of landmarks.

The application of L^{-1} to both the columns of V^T thus specifies the coefficients for the transform between the two sets of landmarks. The coefficients are stored in the matrix "koeff".

- 25 The coefficients are now applied to *all* the pixels in the sought normalized image, pixel-by-pixel, and the corresponding pixel value in the distorted image is determined.

For this calculated pixel in the distorted image, the grey-level (0-255) is determined.

- 30 To determine the grey-level for a non-integer pixel value, some sort of interpolation can be used. In our example a discrete bi-linear interpolation is used. The grey-level thus determined are appointed to the pixel in the sought normalized image.

- The next pixel in the sought normalized image is handled in the same way. In cases
- 35 where the transform is mapping the pixel in the sought image to a pixel-value outside the defined area in the distorted image, the pixel in the sought image is set to 0 (black).

When all pixels are transformed, and appointed a grey-level, the sought image is created and can be plotted and handled as a new image, corrected according to the information from the pair of landmark sets.

Each point in the sought normalized image plane is mapped by a function

5

$$(x, y) \rightarrow (x', y') = (x + f_x(x, y), y + f_y(x, y)),$$

where the f_x and f_y are the function based on $\sum (-1)^k U(|(x, y) - D_k|)$ as viewed in 3 dimensions.

10

Although several examples of embodiments have been described a person skilled in the art will realise then further modifications are possible within the scope of the appended claims.

15

CLAIMS

1. Method for processing digital image data for two-dimensional arrays of sample substance spots and marker substance spots in a plurality of electrophoresis gels by using marker substances having predefined properties, comprising the steps of:
 - 5 - generating marker images represented by marker image data sets comprising coordinate data and signal values corresponding to detected positions and signal values of said marker substance spots in said arrays;
 - processing said marker images to determine a mathematical relation between said marker signals in said marker images such that said respective signals are mapped on
 - 10 each other;
 - generating sample images represented by sample image data sets comprising coordinate data and signal values corresponding to detected positions and signal values of said sample substance spots in said arrays;
 - transforming said sample image signals according to said mathematical relation
 - 15
2. Method for the detection, matching and quantification of sample substances in a plurality of electrophoresis gels by using external marker substances having predefined properties, the method comprising the steps of:
 - combining each of said gels with said sample substances and a plurality of said
 - 20 external marker substances each having a known identity and known characteristics that affect its migration in two-dimensional electrophoresis, which said external marker substances are selected such that they are distinguishable from said sample substances;
 - performing two-dimensional electrophoresis on said gels thus combined with said
 - 25 sample substances and said external marker substances to form a two-dimensional array, each array including said external marker substance spots corresponding to said external marker substances and sample spots corresponding to said sample substances;
 - scanning each array to form a first image of signals corresponding to said external
 - 30 marker substance spots and a second image of signals corresponding to said sample substance spots, the signals of said first image being distinguishable from those of said second image;
 - processing said first image together with the known identity and known characteristics of said external marker to determine a mathematical relation between
 - 35 said first image signals and signals representing said known identity and said known characteristics of said external marker substances such that said respective signals are mapped on each other;
 - transforming said second image signals dependent on said mathematical relation such that the external marker substance spots are positioned as external marker

reference spots on the co-ordinates in the two-dimensional array that correspond to their properties in said electrophoresis gel;

- determining the properties of said sample spots dependent on said external marker reference spots in said transformed second image.

5

3. Method for analysing samples substances by comparison between a first electrophoresis gel and a second electrophoresis gel by using external marker substances having predefined properties, the method comprising the steps of:

- combining each of said gels with said sample substances and a plurality of said

10 external marker substances each having a known identity and known characteristics that affect its migration in two-dimensional electrophoresis, which said external marker substances are selected such that they are distinguishable from said sample substances;

- performing two-dimensional electrophoresis on said gels thus combined with said

15 sample substances and said external marker substances to form a two-dimensional array, each array including said external marker substance spots corresponding to said external marker substances and sample spots corresponding to said sample substances;

- scanning each array to form a marker image of signals corresponding to said external
20 marker substance spots and a sample image of signals corresponding to said sample substance spots, the signals of said marker image being distinguishable from those of said sample image;

- determining a mathematical relation between the signals of the respective marker image of said sample gels, such that the signals corresponding to spots of the same

25 marker substance in the marker images of the first and the second electrophoresis gel are mapped on each other;

- transforming the sample image of the first gel dependent on said mathematical relation, such that the sample images of both gels relate to the same external marker substance positions; and

30 - determining differences between the two electrophoresis gels by directly comparing the transformed sample image of the first gel with the sample image of the second gel.

4. Method for analysing samples substances by comparison between a first

35 electrophoresis sample gel and a second electrophoresis gel by using external marker substances having predefined properties, the method comprising the steps of:

- combining each of said sample gels with a common set of external marker substances each having known properties affecting its migration in two-dimensional electrophoresis;

- performing two-dimensional electrophoresis on each of said sample gels thus combined with said external marker substances to form a two-dimensional array, each array including external marker substance spots corresponding to said external marker substances and sample spots corresponding to said sample substances;
 - 5 -scanning each array to form a marker image of signals corresponding to said external marker substance spots and a sample image of signals corresponding to said sample substances spots, the signals of said marker image being distinguishable from those of said sample image;
 - applying a mathematical relation between the signals of the respective marker image of said sample gels, such that the signals corresponding to spots of the same marker substance in the marker images of the first and the second electrophoresis gel are mapped on each other;
 - 10 - transforming the sample image of the first gel dependent on said mathematical relation, such that the sample images of both gels relate to the same marker substance positions; and
 - 15 - determining differences between the two electrophoresis gels by directly comparing the transformed sample image of the first gel with the sample image of the second gel.
- 20 5. Method for processing digital image data for a two-dimensional array of sample substance spots and landmark substance spots in an electrophoresis gel by using landmark substances having predefined properties, comprising the steps of:
- defining ideal image data comprising co-ordinate data corresponding to ideal positions of the marker substance spots in said array dependent on electrophoresis
 - 25 conditions;
 - generating a marker image represented by marker image data comprising co-ordinate data corresponding to detected positions of said marker substances spots in the array;
 - determining a mathematical relation between the ideal image data and the marker
 - 30 image data, such that the co-ordinate data of said images are mapped onto each other;
 - generating a sample image represented by a sample image data set corresponding to detected signal values in the gel;
 - transforming said sample image according to said mathematical relation.
- 35 6. Method for processing digital image data for two-dimensional arrays of sample substance spots and marker substance spots in a plurality of electrophoresis gels by using external marker substances having predefined properties, the method comprising the steps of:

- generating digital images represented by marker image data sets and sample image data sets comprising coordinate data and signal values corresponding to detected positions and signal values of said marker substance spots and sample substance spots in the arrays.
 - 5 - processing each said digital image to extract the marker substance data sets comprising coordinate data and signal values corresponding to detected positions and signal values of said marker substance spots in the arrays.
 - processing said digital images to determine a mathematical relation between the marker signals in said digital images such that said respective signals are mapped on
 - 10 each other.
 - generating sample images represented by sample image data sets comprising coordinate data and signal values corresponding to detected positions and signal values of said sample substance spots in the arrays
 - transforming said sample image signals according to said mathematical relation
 - 15
7. Method according to claim 6, wherein the step of processing each image to extract marker substance data sets, comprises the process steps of: detecting landmark spots according one or more of the following criteria
- the shapes of the landmark spots, both in two and three dimensions.
 - 20 - the pattern/s of the landmark spots in the gel.
 - a combination of both shapes and pattern/s of the landmark spots in the gel.
 - the positions of the landmark spots in the gel.
 - a combination of both shapes and positions of the landmark spots in the gel.
 - a combination of both positions and pattern/s of the landmark spots in the gel.
 - 25 - a combination of shapes, pattern/s and positions of the landmark spots in the gel..
8. Methods according to claims 1-7, wherein the electrophoresis gels contain a plurality of sets of, in relation to each other distinguishable, sample substances such
- 30 that a plurality of sample images for each electrophoresis gel is acquirable.
9. Method according to claims 1- 8, wherein the step of generating said sample image comprises the step of scanning the array to form a pixel image, and wherein the step of transforming the sample image data signals comprises the step of transforming
- 35 every pixel of said sample image into a transformed image, dependent on said mathematical relation.
10. Method according to claim 8 or 9, wherein said array comprises two different marker substances having different properties, from which different properties co-

ordinate data relating to ideal marker spot positions differing in at least one dimension for given electrophoreses operating conditions can be calculated.

11. Method according to claim 8 or 9, wherein said array comprises a plurality of
5 different marker substances having different properties, from which different properties co-ordinate data relating to ideal marker spot positions differing in two dimension for given electrophoreses operating conditions can be calculated.

12. Method according to claim 11, wherein, dependent on the electrophoreses
10 operating conditions, a set of marker substances is selected, comprising said plurality of different marker substances, dependent on their corresponding co-ordinates of in the ideal image data.

13. Method according to claim 8, wherein the step of normalising the sample image
15 comprises the process steps of:

- selecting a first pixel in the image plane defined by said ideal image data;
- mapping said first pixel to the sample image;
- reading the detected signal value for the mapped first pixel;
- assigning said detected signal value to said first pixel in the image plane of the ideal
20 image data; and
- repeating these process steps for each pixel in the image plane.

14. Method according to claim 13, wherein the step of reading the detected signal
value for the mapped first pixel comprises the step of:

25 - establishing a detected signal value for the mapped first pixel dependent on the signal value of at least one pixel in the sample image adjacent the mapped first pixel.

15. Method according to claim 8, wherein the step of normalising the sample image
comprises the process steps of:

30 - selecting a first pixel in the sample image;

- reading the detected signal value for said first pixel;
- mapping said first pixel to the image plane defined by said ideal image data;
- assigning said detected signal value to the mapped first pixel in the image plane of the ideal image data; and

35 - repeating these process steps for each pixel in the sample image.

16. Method according to claim 8, wherein the step of normalising the sample image
comprises the process steps of:

- selecting a first pixel in the image plane defined by said ideal image data;

- reading the detected signal value for the mapped first pixel;
 - mapping said first pixel to the sample image;
 - assigning said detected signal value to said first pixel in the image plane of the ideal image data; and
- 5 - repeating these process steps for pixels in the image plane defining an object consisting of sample substance spots and/or marker substance spots.

17. Method according to claim 10, further comprising the steps of:
- determining the signal value for a first pixel in the ideal image plane dependent on
- 10 the signal value of at least one mapped pixel in the ideal image plane adjacent said first pixel in the ideal image plane; and
- repeating this determination process for each pixel in the ideal image plane.

18. Method according to claims 1-17, wherein the marker substances are non-protein
- 15 compounds.

19. The method as recited in any of the previous claims, wherein said marker substance is an compound comprising a least a functional unit.
- 20 20. The method as recited in any of the previous claims, wherein said marker substance is an compound comprising a least a monomer unit and a functional unit.

21. Method according to one or more of the preceding claims wherein the detection of the landmark spots is done by monitoring the shapes of the landmark spots, both in
- 25 two and three dimensions.

22. Method according to one or more of the preceding claims wherein the detection of the landmark spots is done by monitoring the pattern(-s) of the landmark spots in the
- 30 gel.

23. Method according to one or more of the preceding claims wherein the detection of the landmark spots is done by monitoring a combination of both shapes and pattern(-s) of the landmark spots in the gel.

- 35 24. Method according to one or more of the preceding claims wherein the detection of the landmark spots is done by monitoring the positions of the landmark spots in the gel.

25. Method according to one or more of the preceding claims wherein the detection of the landmark spots is done by monitoring a combination of both shapes and positions of the landmark spots in the gel.

5 26. Method according to one or more of the preceding claims wherein the detection of the landmark spots is done by monitoring a combination of both positions and pattern(-s) of the landmark spots in the gel.

10 27. Method according to one or more of the preceding claims wherein the detection of the landmark spots is done by monitoring a combination of shapes, pattern(-s) and positions of the landmarks spots in the gel.

15 28. A computer program product for use in a computer system, comprising computer program code means for executing the computer system to process digital image data for a two-dimensional array of sample substance spots and marker substance spots in an electrophoresis gel, by performing the steps of:

- accessing coordinate data for a marker image, relating to detected positions of marker spots of a predetermined substance in the array, dependent on electrophoresis operating conditions;
- 20 - accessing coordinate data for another marker image, relating to detected positions of marker spots of said predetermined substance in the array;
- determining a mathematical relation between said marker images, such that the coordinate data of said images are mapped onto each other;
- generating a sample image represented by a sample image data set corresponding to
- 25 detected signals in the gel;
- transforming the sample image by transforming it dependent on said mathematical relation.

30 29. Computer program product according to claim 28, further comprising computer program code means for executing the computer system to perform the steps of any of the claims 1 – 27.

1/2




Fig. 1




Fig. 2

BEST AVAILABLE COPY




Fig. 3




Fig. 4

INTERNATIONAL SEARCH REPORT

International application No.

PCT/SE 03/00029

A. CLASSIFICATION OF SUBJECT MATTER

IPC7: G01N 27/447, G06K 9/64

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC7: G01N, G06K

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

SE,DK,FI,NO classes as above

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

EPO-INTERNAL, WPI DATA

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	WO 0107920 A2 (BIO-RAD LABORATORIES, INC.), 1 February 2001 (01.02.01), see the whole document --	1-29
Y	US 5073963 A (DAVID W. SAMMONS ET AL), 17 December 1991 (17.12.91), see the whole document --	1-29
Y	JOSSO, B. et al "Automatic 2-D Gel Registration Using Distance Minimisation of Image Morphing" Coherent and Electro-optic Research Group, IEEE, 19-21 July 2000 Pages 357-361 see the whole document --	1-29



Further documents are listed in the continuation of Box C.



See patent family annex.

* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier application or patent but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

31 March 2003

Date of mailing of the international search report

04-04-2003

Name and mailing address of the ISA/

Swedish Patent Office

Box 5055, S-102 42 STOCKHOLM

Facsimile No. +46 8 666 02 86

Authorized officer

Henrik Eriksson/mj

Telephone No. +46 8 782 25 00

INTERNATIONAL SEARCH REPORT

International application No.

PCT/SE 03/00029

C (Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	Thompson, A. et al "Information Extraction from 2D Electrophoresis Images" Proceedings of the 20th Annual International Conference of the IEEE Engineering in Medicine and Biology Society, Vol 20, No 2, 1998 see the whole document --	1-29
P,Y	WO 0219257 A1 (LARGE SCALE PROTEOMICS CORPORATION), 7 March 2002 (07.03.02) --	1-29
A	WO 9823950 A1 (OXFORD GLYCOSCIENCES), 4 June 1998 (04.06.98), see the whole document -- -----	1-29

INTERNATIONAL SEARCH REPORT

Information on patent family members

30/12/02

International application No.

PCT/SE 03/00029

Patent document cited in search report			Publication date	Patent family member(s)		Publication date
WO	0107920	A2	01/02/01	AU	6608500 A	13/02/01

US	5073963	A	17/12/91	AU	8001991 A	31/12/91
				WO	9119274 A	12/12/91

WO	0219257	A1	07/03/02	AU	8846501 A	13/03/02
				US	6404905 B	11/06/02
				US	2002114501 A	22/08/02

WO	9823950	A1	04/06/98	AU	713259 B	25/11/99
				AU	5230098 A	22/06/98
				EP	0941477 A	15/09/99
				GB	9624927 D	00/00/00
				JP	2001504938 T	10/04/01
				NO	992583 A	28/07/99
				US	6064754 A	16/05/00
				US	6278794 B	21/08/01
				US	6480618 B	12/11/02
				US	2002191825 A	19/12/02
				ZA	9710792 A	01/12/98
